

## DENSO ACRYLIC TOPCOAT

### Acrylic Based Topcoat

#### Description

An acrylic paint designed for use in various applications within Denso coating systems. Pigmented, water-based, high opacity, acrylic paint. Available in white, black, grey or misty green.

#### Uses

An integral component in various Denso coating systems as a topcoat finish.

#### Features

- Accommodates some vibration and movement of substrate
- Resistant to mineral acids, alkalis and salts
- Will adhere and remain attached to acrylic backed tapes

#### Application

Ensure the substrate is prepared as per directed by the proposed coating system.

Thoroughly stir the paint in its container to ensure uniformity prior to use. Apply by brush, roller or airless spray.

Do not apply when ambient temperature is below 10°C or when relative humidity exceeds 90%. Allow a dwell time of 2 hours at 20°C before attempting to recoat. Coating is usually touch dry in 30 minutes.

Expected consumption rate is 3.0 m<sup>2</sup>/L.



# Denso Acrylic Topcoat

## TECHNICAL DATA

<b>PROPERTIES</b>	<b>VALUE</b>
Solids Content (w/w)	38 %
Density	1.08 kg/L
Flash Point	100°C
Colour	Black, White, Grey, Misty Green

### STORAGE AND HANDLING:

Store the containers in a dry, well ventilated area below 35°C.  
The containers should be kept tightly sealed.

PACKAGING: 4 L (4/carton), 15 L.



**DENSO (AUSTRALIA) PTY LTD**

77 - 95 National Boulevard

Campbellfield, VIC 3061

Tel: +61 3 9356 7600

Fax: +61 3 9356 7699

[www.densoaustralia.com.au](http://www.densoaustralia.com.au)

***A Member of the Winn & Coales International***

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.